ROBERT USHER

said housing includes a foot portion which extends rearward beyond connecting portions of said electrical contacts,

said connecting portions to be connected to said circuit board, and said mount bottom surface extends to a rear end of said foot portion

and wherein said fitting part of said housing has a lower surface and said mount bottom surface of said housing is located at a higher level than said lower surface of said fitting part of said housing, and a step is provided between said lower surface of said fitting part and said mount bottom surface, the housing having a contact- retaining portion with a thick, vertically extending wall in which contact-retaining portion said contacts are retained tightly, said step being formed on a bottom of the wall vertically aligned below the contact-retaining portion.

Cancel claims 2 and 3

Add new claim 4

4 (New)A connector according to claim 1 wherein said contacts are retained tightly in the contact-retaining portion thick wall by press-fitting therein.

Remarks

10/09/2002 11:55

Claim 1 has been amended by inclusion of the limitations of original claims 2 and 3 and adding emphasis that the step is vertically aligned below the contact retaining portion being formed on a bottom of a thick, vertically extending wall thereof in which the contacts are retained tightly. Amendment has also been made to overcome the rejections under 35 USC 112.

New claim 4 particularizes that the contacts are press- fit in the wall of the contact-retaining portion.

In contending the rejection of claims 1-3 as anticipated under 35 USC 102 by Hashimoto, as it may be applied to the new claims it is pointed out that the step of the reference is not formed on a bottom of the wall vertically aligned below the contactretaining portion of the housing but is located rearward of the contact retaining portion. Thus, the rejection under 35 USC 102 cannot apply to claim 1 as amended.

Contact retaining portions of electrical connector housings are relatively massive blocks of plastic providing a thick wall as compared with the remainder of the housing